

Technical Data Sheet

NORC RASANT *db* **SAE 10W60 API SN/CF** **Fully Synthetic Racing Engine Oil**

PRODUCT DESCRIPTION

NORC RASANT *db* SAE 10W60 is a high performance fully synthetic based formulation racing engine oil for an ultimate engine protection. It protects against friction, heat and corrosion, keeping engines healthy and efficient. NORC precisely used an advanced additive technology that reduces carbon sludge build up even under severe driving conditions. It is optimally suited for use in high stress environments.

NORC RASANT *db* SAE 10W60 is specially formulated using the finest fully synthetic base oils and state of the art additive technology for optimum operation in benzin and diesel engines with or without turbocharger, meeting or exceeding the service requirements of API SN/CF.

BENEFITS

- Race and track tested
- Outstanding anti-wear properties
- Excellent high-heat protection and oil stability
- Optimum operation under severe driving conditions
- Long drain interval
- Rapid oil flow and excellent low friction characteristics
- Low oil & fuel consumptions
- Enhance engine performance and efficiency
- Protect against carbon sludge build-up
- Prolong engine performance and longevity

Technical Data Sheet

NORC RASANT *db* **SAE 10W60 API SN/CF** **Fully Synthetic Racing Engine Oil**

SPECIFICATIONS

API SN/CF
ACEA A3/B3/B4
MB 229.3
VW 501.01/505.00
FIAT 9.55535-H3

TECHNICAL DATA SHEET

| PROPERTY | UNIT | TEST METHOD | SAE 10W60 |
|-----------------------------|-------------|--------------------|------------------|
| Density @ 15°C | Kg/L | ASTM D4052 | 0.850 |
| Kinematic Viscosity @ 40°C | Cst | ASTM D445 | 183 |
| Kinematic Viscosity @ 100°C | Cst | ASTM D445 | 25 |
| Viscosity Index | | ASTM D2270 | 169 |
| Flash Point, COC | °C | ASTM D92-05A | > 210 |
| Pour point | °C | ASTM D97 | < -33 |

The above data is just an indication based on production, and does not considered to be actual specification. "NANO OIL REFINING COMPANY NORC GmbH" holds its right to make modifications.