

Technical Data Sheet

NORC BREMSOL DOT 4 **FULLY SYNTHETIC BRAKE FLUID**

PRODUCT DESCRIPTION

NORC BREMSOL DOT 4 is a 100% synthetic high performance brake fluid with an elevated dry boiling point of 250°C, and a wet boiling point of 168°C. It provides enhanced corrosion protection for all hydraulic brake systems.

NORC BREMSOL DOT 4 is precisely developed to offer an unmatched performance. As well as, an enhanced braking characteristics with superior protection and durability. It is for use in hydraulic clutch systems, according to manufacturer's instructions.

BENEFITS

- 100% Synthetic.
- High boiling point.
- Minimal vapor formation at elevated temperatures.
- Excellent protection against acidic oxidation.
- Excellent corrosion protection.
- Outstanding brake system performance.
- Extended life and reliability.
- Excellent performance under severe braking pressure.
- Compatible with most brake system rubber materials.
- Minimize leakage.
- High thermal and oxidation stability.
- Prevention against formation of deposits.

Technical Data Sheet

NORC BREMSOL DOT 4 **FULLY SYNTHETIC BRAKE FLUID**

SPECIFICATIONS

US FMVSS 116 DOT 4 / DOT 3

SAE J 1704 / J 1703

ISO 4925

TECHNICAL DATA SHEET

PROPERTY	UNIT	TEST METHOD	DOT 4
Density @ 20°C	Kg/L	DIN 51 757	1.04
Viscosity @ -40°C	Cst	DIN EN ISO 3104	1200
Viscosity @ 100°C	Cst	DIN EN ISO 3104	2.17
Dry Boiling Point	°C	FMVSS 116	250
Wet Boiling Point	°C	FMVSS 116	168

The above data is just an indication based on production, and does not considered to be actual specification. "NANO OIL REFINING COMPANY NORC GmbH" holds its right to make modifications.