

Technical Data Sheet

NORC ENORM *db* **SAE 5W30 API SN/CF** **Fully Synthetic Engine Oil**

PRODUCT DESCRIPTION

NORC ENORM *db* SAE 5W30 is a unique fully synthetic lubricating engine oil for an ultimate engine protection and performance.

NORC ENORM *db* SAE 5W30 is a multi-grade engine oil especially developed and formulated with the finest synthetic base stocks and advanced additive technology, to keep engines healthy and efficient. It reduces carbon sludge build up under harsh driving conditions. It provides superior low friction with strengthened oil film for greater engine response and fuel efficiency.

NORC ENORM *db* SAE 5W30 fulfills or exceeds the service requirements of API SN/CF and it is excellently suited for use in passenger cars and light trucks, equipped with benzin and diesel engines, both turbocharged and non-turbocharged.

BENEFITS

- Excellent wear and high heat protection
- Excellent viscosity retention
- Excellent engine protection under harsh driving conditions
- Long drain intervals
- Reduce carbon sludge build up
- Low oil & fuel consumption
- Superior low friction characteristics
- Improve engine efficiency and longevity

Technical Data Sheet

NORC ENORM *db* **SAE 5W30 API SN/CF** **Fully Synthetic Engine Oil**

SPECIFICATIONS

API SN/CF
ACEA A3/B4
MB 229.5
VW 502.00/505.00
BMW LL-98

TECHNICAL DATA SHEET

PROPERTY	UNIT	TEST METHOD	5W30
Color		ASTM D1500	< 3.5
Density @ 15°C	Kg/L	ASTM D4052	0.860
Kinematic Viscosity @ 40°C	Cst	ASTM D445	68
Kinematic Viscosity @ 100°C	Cst	ASTM D445	11.2
Viscosity Index		ASTM D2270	164
Flash Point, COC	°C	ASTM D92-05A	> 200
Pour point	°C	ASTM D97	< -39

The above data is just an indication based on production, and does not considered to be actual specification. "NANO OIL REFINING COMPANY NORC GmbH" holds its right to make modifications.