

# Technical Data Sheet

## **NORC TAKT *db*** **SAE 10W40 API SN/CF** **Semi Synthetic Engine Oil**

### **PRODUCT DESCRIPTION**

**NORC TAKT *db* SAE 10W40** is high performance light running HC synthetic engine oil designed for use in modern engines with tight tolerances. Its unique formulation provides excellent performance, protection and fuel economy properties.

**NORC TAKT *db* SAE 10W40** is premium synthetic blend multi-grade engine oil, precisely developed and formulated with advanced additive technology to ensure excellent viscosity retention and thermal stability under all driving conditions.

**NORC TAKT *db* SAE 10W40** fulfills or exceeds the service requirements of API SN/CF and it is excellently suited for use in passenger cars and light trucks, equipped with benzin and diesel engines, both turbocharged and non-turbocharged.

### **BENEFITS**

- Excellent wear and high heat protection
- Excellent Viscosity retention
- Excellent engine protection under different driving conditions
- Low oil & fuel consumptions
- Excellent Low friction characteristics
- Thermal Stability
- Enhanced anti-wear properties
- Improved engine cleanliness
- Improved engine efficiency and performance

# Technical Data Sheet

## **NORC TAKT *db*** **SAE 10W40 API SN/CF** **Semi Synthetic Engine Oil**

### **SPECIFICATIONS**

API SN/CF  
ACEA A3/B3/B4  
MB 229.1  
VW 501.01/505.00  
FORD ESE-M2C 153-E

### **TECHNICAL DATA SHEET**

<b>PROPERTY</b>	<b>UNIT</b>	<b>TEST METHOD</b>	<b>SAE 10W40</b>
Density @ 15°C	Kg/L	ASTM D4052	0.868
Kinematic Viscosity @ 40°C	Cst	ASTM D445	91.8
Kinematic Viscosity @ 100°C	Cst	ASTM D445	14.2
Viscosity Index		ASTM D2270	137
Flash Point, COC	°C	ASTM D92-05A	> 210
Pour point	°C	ASTM D97	< -36

The above data is just an indication based on production, and does not considered to be actual specification. "NANO OIL REFINING COMPANY NORC GmbH" holds its right to make modifications.