

Technical Data Sheet

NORC RASANT *db* SAE 10W60 ACEA A3/B3/B4 Fully Synthetic Racing Engine Oil

PRODUCT DESCRIPTION

NORC RASANT *db* SAE 10W-60 is a high performance fully synthetic based formulation racing engine oil for an ultimate engine protection. It protects against friction, heat and corrosion, keeping engines healthy and efficient. NORC precisely used an advanced additive technology that reduces carbon sludge build up even under severe driving conditions. It is optimally suited for use in high stress environments.

NORC RASANT *db* SAE 10W-60 is specially formulated using the finest fully synthetic base oils and state of the art additive technology for optimum operation in benzin and diesel engines with or without turbocharger, meeting and / or exceeding the service requirements of ACEA A3/B3/B4.

BENEFITS

- Excellent high-heat protection and oil stability
- Enhance engine performance and efficiency
- Long drain interval
- Low oil & fuel consumptions
- Outstanding anti-wear properties
- Optimum operation under severe driving conditions
- Protect against carbon sludge build-up
- Prolong engine performance and longevity
- Race and track tested
- Rapid oil flow and excellent low friction characteristics



Technical Data Sheet

NORC RASANT *db* SAE 10W60 ACEA A3/B3/B4 Fully Synthetic Racing Engine Oil

SPECIFICATIONS

ACEA A3 / B3 / B4 API SN / CF MB 229.3 VW 501.01 / 505.00 FIAT 9.55535-H3

TECHNICAL DATA SHEET

PROPERTY	UNIT	TEST METHOD	SAE 10W-6 <mark>0</mark>
Density @ 15°C	Kg / L	ASTM D4052	0.850
Kinematic Viscosity @ 40°C	Cst	ASTM D445	183
Kinematic Viscosity @ 100°C	Cst	ASTM D445	2 <mark>5</mark>
Viscosity Index		ASTM D2270	1 <mark>69</mark>
Flash Point, COC	°C	ASTM D92	> <mark>230</mark>
Pour Point	°C	ASTM D97	<mark>< - 33</mark>

The above data is just an indication based on production, and does not considered to be actual specification. "NANO OIL REFINING COMPANY NORC GmbH" holds its right to make modifications.