

Technical Data Sheet

NORC ENORM *db* **SAE 5W-50 ACEA A3/B3/B4** **Fully Synthetic Engine Oil**

PRODUCT DESCRIPTION

NORC ENORM *db* SAE 5W-50 is a fully synthetic based formulation that protects against friction, heat and corrosion, keeping engines healthy and efficient. NORC additive technology reduces carbon or sludge build up even under severe driving conditions, and optimally suited for high stress environments.

NORC ENORM *db* SAE 5W-50 is manufactured using highest quality fully synthetic base stocks and state of the art additive technology. The modern manufacturing process ensures a top quality finished product.

NORC ENORM *db* SAE 5W-50 PAO based formulation is especially designed for use in an advanced passenger car and diesel engines, both turbocharged and non-turbocharged. It is engineered to fulfill and / or exceed the performance requirements of ACEA A3/B3/B4.

BENEFITS

- Excellent wear & high heat protection
- Excellent viscosity retention
- Excellent engine protection under harsh driving conditions
- Improve engine efficiency and longevity
- Long drain interval
- Low oil & fuel consumptions
- Reduce carbon sludge build-up
- Superior low friction characteristics

Technical Data Sheet

NORC ENORM *db*

SAE 5W-50 ACEA A3/B3/B4

Fully Synthetic Engine Oil

SPECIFICATIONS

ACEA A3 / B3 / B4

API SN / CF

MB 229.3

VW 502.00 / 505.00

PORSCHE A40

BMW LL-01

TECHNICAL DATA SHEET

PROPERTY	UNIT	TEST METHOD	SAE 5W-50
Density @ 15°C	Kg / L	ASTM D4052	0.854
Kinematic Viscosity @ 40°C	Cst	ASTM D445	115
Kinematic Viscosity @ 100°C	Cst	ASTM D445	18.5
Viscosity Index		ASTM D2270	180
Flash Point, COC	°C	ASTM D92	> 230
Pour Point	°C	ASTM D97	< - 36

The above data is just an indication based on production, and does not considered to be actual specification. "NANO OIL REFINING COMPANY NORC GmbH" holds its right to make modifications.