

Technical Data Sheet

NORC ENORM-C3 db

SAE 5W-40 ACEA C3

Fully Synthetic Engine Oil

PRODUCT DESCRIPTION

NORC ENORM-C3 db SAE 5W-40 is a fully synthetic based formulation that protects against friction, heat and corrosion, keeping engines healthy and efficient. NORC additive technology reduces carbon or sludge build up even under severe driving conditions.

NORC ENORM-C3 db SAE 5W-40 is manufactured using highest quality fully synthetic base stocks and state of the art additive technology. This ensures a finished product with unmatched performance level.

NORC ENORM-C3 db SAE 5W-40 is designed for an advanced passenger cars gasoline and diesel engines, both turbocharged and non-turbocharged including engines with diesel particulate filters DPF meeting requirements of ACEA C3. Also, suitable for engines equipped with catalytic converters, and Exhaust Gas Recirculation (EGR) devices.

BENEFITS

- Excellent wear and high heat protection
- Excellent viscosity retention
- Excellent engine protection under harsh driving conditions
- Improve engine efficiency and longevity
- Long drain interval
- Low oil & fuel consumptions
- Reduce carbon sludge build up
- Superior low friction characteristics

Technical Data Sheet

NORC ENORM-C3 db

SAE 5W-40 ACEA C3

Fully Synthetic Engine Oil

SPECIFICATIONS

ACEA C3-12, A3-B4-04
 API SN / CF
 RENAULT RN 0700 / 0710
 FORD WSS-M2C917-A
 FIAT 9.55535-S2
 OPEL GM DEXOS 2
 VW 502.00 / 505.00 / 505.01
 MB 229.51
 BMW LL-04
 PORSCHE A40

TECHNICAL DATA SHEET

PROPERTY	UNIT	TEST METHOD	5W-40
Density @ 15°C	Kg / m ³	DIN 51 757	854
Kinematic Viscosity @ 40°C	mm ² / s	DIN 51 562	81.5
Kinematic Viscosity @ 100°C	mm ² / s	DIN 51 562	13.5
Viscosity Index		DIN ISO 2909	169
CCS @ -30°C	mPa.s	DIN 51 377	6240
Flash Point	°C	DIN ISO 2592	> 230
Pour Point	°C	DIN ISO 3016	< - 36

The above data is just an indication based on production, and does not considered to be actual specification. "NANO OIL REFINING COMPANY NORC GmbH" holds its right to make modifications.